

1/5 OVERVIEW



8561V



The kit consists of No. 1 Quadra external video entry unit for ViP kits art. 4899K, No. 1 power supply unit art.1441B, No. 1 network switch art.1440 and No. 1 Mini handsfree Wi-Fi monitor art. 6742WK. The kit is pre-programmed and ready for use. The kit is expandable with other VIP catalog products. Compatible with H.264 video format.

AWARDS









8561V

QUADRA KIT AND MINI WI-FI/GW. VIP SYSTEM

KIT PRODUCT



6742WK

White HF Mini Monitor WI-FI/GW for ViP KIT

MAIN FEATURES - 6742WK			
Audio system:	No		
Audio/video system:	Yes		
Flush-mounted:	No		
Wall-mounted:	Yes		
Desk base-mounted:	Yes		
Hands-free function:	Yes		
Induction loop function:	Yes		
Type of display:	LCD		
Display size (inch):	4,3" 16:9		
Touch screen display:	Yes		
Display resolution HxV (inch):	480x272		
B/W or colour display:	Color		
Product colour:	White		
Sensitive Touch technology:	Yes		
Total buttons:	8		
LED signaling (no.):	4		
Wi-Fi Port:	Yes		
Comaptibility with Video Entry Comelit App:	Yes		



4899K

QUADRA external unit for ViP KIT

MAIN FEATURES - 4899K		
Type:	Monoblock entrance panel	
Material:	Die-cast aluminium	
Wall-mounted:	Yes	
Camera:	Colors	





8561V

QUADRA KIT AND MINI WI-FI/GW. VIP SYSTEM

MAIN FEATURES - 4899K				
naling LED: Call sent, lock-release activated, audio activated, system busy				
Power supply:	PoE (Class 0) / VIP (37 ÷ 57 VDC)			
Buttons to call:	Yes			
Total buttons:	1			
Loudspeaker volume control:	Yes			

1440

NETWORK SWITCH 4 PORT



PoE Ethernet switch with 2 ports (10/100 Mb) and 4 ports (10 MB). Dimensions $66 \times 85 \times 35 \text{ mm}$

MAIN FEATURES - 1440			
Product height (inch):	3.5		
Product width (inch):	2.83		
Product depth (inch):	2.44		
Operating temperature (°F):	41 ÷ 104		
RH max operating humidity (%):	25 ÷ 75		
DIN rail mounted:	Yes		
DIN modules (no.):	4		

1441B

30W VIP SYSTEM POWER SUPPLY UNIT

Power supply unit with 110Vac/240Vac input and 48Vdc output. 30W power. DIN bar power supply unit (4 DIN modules). Dimensions: 72x93x56mm

MAIN FEATURES - 1441B			
Alternating input voltage (VAC):	110÷240		
Number of DIN modules:	4		







8561V

QUADRA KIT AND MINI WI-FI/GW. VIP SYSTEM

ACCESSORIES



4899K

QUADRA external unit for ViP KIT



6742WK

White HF Mini Monitor WI-FI/GW for ViP KIT



4791

Adapter plate for Quadra

Plate allowing installation of the Quadra external unit in 1- and 2-module flush-mounted boxes by Comelit, Bticino and Urmet. Dimensions 137x236 mm



4792

RAIN SHIELD FOR QUADRA ENTRANCE PANEL

Rain shield in painted aluminum for Quadra entrance panel, grey colour. Dimensions (W \times H \times D): 99 \times 210 \times 41 mm.



4793B

BLACK FACEPLATE FOR QUADRA ENTRANCE PANEL

Black faceplate for Quadra entrance panel



4793C

CORTEN FACEPLATE FOR QUADRA ENTRANCE PANEL

Corten faceplate for Quadra entrance panel





8561V

QUADRA KIT AND MINI WI-FI/GW. VIP SYSTEM

ACCESSORIES



4793A

ALUMINIUM FACEPLATE FOR QUADRA ENTRANCE PANEL

Aluminium colour faceplate for Quadra entrance panel

1217

NAME TAG SHEETS FOR QUADRA ENTRANCE PANEL

The kit contains 10 sheets of adhesive labels for nameplates



1235A

NAMEPLATE LABEL PRINTING SOFTWARE

Dedicated software for the creation and printing of nameplate and information labels for Ikall, Vandalcom, Quadra and 316 Analog entrance panels. Requires use of adhesive labels art.1217, 1218, 1219 or art.1220. This software is available to download free of charge from the Comelit website



6711WV

ADAPTER PLATE FOR MINI HANDSFREE

Adapter plate to finish the installation of the Mini Handsfree monitor in case of replacement of flush-mounted or wall-mounted Planux, Smart and Icona monitors. White color. Dimensions: 170x220x3 mm.



6720V

Bracket for routing Mini HF ViP external cables

Wall bracket for ViP system hands-free Mini monitor; allows through-routing of external cables.



6732V

Desk base for hands-free Mini ViP monitor

Desk base for desktop conversion of ViP system hands-free Mini monitor. Complete with 1x 2 metre cable with RJ45 connector to connect monitor terminals to the coupler or residential series socket.